



## RGL3

### TWIN LEG WEBBING LANYARD & SHOCK ABSORBER

**This twin leg lanyard is produced using our anti-bacterial protection webbing.**

An industry standard, and usually the minimum equipment issued/required with a harness for anyone working at height.

The extra leg allows progression between anchor points by means of double clipping, and also optimum safety by ensuring the user is always connected.

The shock absorber pack will deploy in the event of a fall limiting the impact force on the user.

This system is generally used for tower climbing, steel erecting, scaffolding and maintenance to open structures.



Shock absorber

Accredited to: EN 355:2002

Material: 26mm RIDGE Protect anti-bacterial polyester\*

Fittings: 17mm steel screwgate karabiner (RGK1)

Any other compatible EN 362 connectors

Max arrest force: <6kN

Length(s) (including connectors): 1.4m (up to 140kg user)  
1.8m (up to 100kg user)

Other lengths available upon request, but would require a minimum order of 30 pieces. Lengths range from 1m to 1.4m for 140kg users and from 1.5m to 1.8m for 100kg users.

\*14 times reduction in bacterial growth, according to ISO 20743:2013 contact with *K.pneumoniae*, commonly associated with healthcare infections such as *E.coli*



RIDGEGEAR LIMITED

📍 Nelson Street, Leek, Staffordshire, ST13 6BB, UK

☎ +44 (0)1538 384 108

✉ sales@ridgegear.com

🌐 ridgegear.com

